



Since 1958

Carlack Products Australia
Distributors of quality car care products

Product Application Instructions - Carlack Complete 68 polish



Step 1. Wash and dry your vehicle. We recommend Carlack Car Shampoo to wash your vehicle. Ensure you follow local regulations regarding water usage and wash your car on a soft surface.

We recommend that polishes are applied with the vehicle in a shaded area. Applying polish in direct sunlight will not affect the finished results of the Carlack range; the polish tends to harden and therefore requires greater effort to remove.

Step 2. Evaluate the quality of the paint finish on your vehicle. Do this by wiping your fingers over the paint surface and feel for a rough finish on your paintwork. If the paint surface feels abrasive you may need to use a stronger (cutting) polish. We recommend using Carlack Cutting polish for this task. If cutting polish is not required follow the instructions below.

Carlack Complete 68 polish is a very easy product to use. As with any polish, the longer the painted surface is left unprotected the more effort is required to rejuvenate the paintwork. To apply Carlack Complete 68 polish we recommend using a kitchen sponge (Chux or similar) without the scouring pad on one side! A new sponge works well with older or contaminated paint as the sharper edge on the sponge pores assists the cleaning of the paint. An older sponge is just fine for good condition paint. **Tip:** When you have finished polishing your car store the sponge in a zip-lock bag for next time!

Application:

Dampen the sponge and squeeze out as much water as possible. Apply a small amount of Carlack Complete 68 polish to the sponge and then apply the polish to the paint in gentle, overlapping circles. Cover one panel at a time and allow the polish to dry off for several minutes. The polish will dry to a light haze and is now ready to remove.

Removal:

Using a soft cotton cloth (flanalette or an old t-shirt) or microfibre cloth, gently wipe over the applied areas in a circular motion frequently turning the removal cloth. Your result should be a smooth to the touch finish and a brilliant shine. If the paint surface does not feel smooth, reapply a second coat of polish, this timing using a newer sponge.

Carlack Complete 68 polish will give you a long lasting shine and a paint surface that is now easier to wash and keep clean.

The Carlack Car Care range also offers glass and interior cleaners and protectors.

For more information on other Carlack products go to our website –

www.carlackproducts.com.au

P: 0410 992 535

E: enquiries@carlackproducts.com.au

W: carlackproducts.com.au

Correspondence: P.O. Box 44 Penshurst NSW Australia 2222

ABN: 93 601 075 236